Ricoh IFPD D8600BK Competitive Matrix

	Diada DOCOORY		Sk Competitive Matrix	Consult Present 7000 Pr	Ois sa Makan Barrat OF
Model	Ricoh D8600BK \$10,125 – IFPD only	Sharp PN-L851H	Clevertouch UX Pro 86"	Smart Board 7086 Pro	Cisco Webex Board 85s
Street Price	\$10,125 - IFPD only \$1,910 - Windows 10 Business Controller \$1,535 - Windows 10 i5 Controller \$1,989 - Windows 10 i7 Controller	\$9,990 – IFPD w/ Embedded Android Controller	INA - IFPD w/ Embedded Android Controller	\$9,598 w/ Embedded Windows Controller	\$15,179 plus Cisco Webex Service Subscription
Display Specifications	0011 41- 4- 1- 1 / 40-0	05 4: / 40:0	0011 dia da na 1 / 400	0011 1:	05% dia 42.54 / 40.0
Panel Size / Aspect Ratio	86" diagonal / 16:9	85" diagonal / 16:9	86" diagonal / 16:9	86" diagonal / 16:9	85" diagonal / 16:9
Supported Display Orientations Screen Type	Horizontal LCD	Horizontal, Vertical (Portrait) LCD	Horizontal LCD	Horizontal LCD	Horizontal LCD
Back Light	LED	LED, Direct Lit	LED	LED	LED
Maximum Resolution	3,840 x 2,160 dpi (4K)	3,840 x 2,160 dpi (4K)	3,840 x 2,160 dpi (4K)	3,840 x 2,160 dpi (4K)	3,840 x 2,160 dpi (4K)
Maximum Display Colors	1.07 billion (10 bit color processing)	1.07 billion	1.07 billion	NA	1.07 billion
Contrast Ratio	1,200:1	5,000:1	1,200:1	5,000:1	14,000:1
Brightness	410 cd/m ²	350 cd/m ²	400 cd/m ²	3,000.1 360 cd/m ²	350 cd/m²
Angle of View	Left/Right: 178°, Up/Down: 178°	Left/Right: 178°, Up/Down: 178°	Left/Right: 178°, Up/Down: 178°	Left/Right: 178°, Up/Down: 178°	Left/Right: 178°, Up/Down: 178°
Touch Screen Technology	Shadow Sense – 2 nd Generation	InGlass™ by FlatFrog	High Precision Technology	HyPr (proprietary)	Capacitive Touch
Touch Screen Response Speed	8 milliseconds	9.5 milliseconds	8 milliseconds	8 milliseconds	6.5 milliseconds
Maximum Number of	10 points (TouchPanel)				
Simultaneous Touch Points	4 points (using IWB Software)	20 points	20 points	16 points	1 or 2 points
Built-in Camera	No	No	No	No	Yes
Built-in Microphone	No	No	Standard	No	Yes
Built-in Speakers	12 W x 2 (Bottom)	10 x 2	15 W x 2	10 W x 2	INA W x 2
Installation Type	Wall mount or optional rolling stand	Wall mount or optional 3rd Party stand	Wall mount or optional 3rd Party stand	Wall mount or optional 3rd Party stand	Wall mount or optional 3rd Party stand
Advanced Features					
Finger Writing & Page Control	Supported	Supported	Supported	Supported	Standard
Passive Pen Writing	Supported	Supported	Supported	Supported	Standard
Intelligent Character Recognition	Supported	Supported	Supported	Not Supported	INA
Daisy Chain Display & Control	Supported	Not Supported	Supported	Supported	Supported
Picture In Picture/Picture By Picture	Supported	Supported	Supported	Supported	Supported
Page Creation/Mark-up/Saving	Supported	Supported	Supported	Supported	Supported
Remote Interactive Collaboration	Supported with IWB Remote License	Supported	Supported	Supported	Supported w/ Cisco Webex Teams app
Real-time Video Conferencing	Supported with IWB Remote License	3rd Party Supported	3rd Party Supported	Supported	Supported w/ Cisco Webex Teams app
Participation via Remote Devices Display Connectivity Terminals	Supported with IWB Remote License	Supported	Supported	Supported	Supported w/ Cisco Webex Teams app
Display Input Terminals	 Mini D-Sub 15-pin (VGA) x 1 HDMI x 1 (HDCP compliant) DisplayPort x 1 (HDCP compliant) DVI-D x 1 (HDCP compliant) USB 3.0 Type B x 1 (for Touchscreen) USB 3.0 Type A x 4 (side) USB 2.0 Type A x 4 (2 rear, 2 side) OPS x 1 for Controller Module OPS x 1 for Capture Module [Additional input & network interfaces on opt. Controller & Capture modules] 	 Mini D-Sub 15-pin (VGA) x 1 HDMI x 2 (HDCP compliant) DisplayPort x 1 (HDCP compliant) USB 2.0 Type B x 1 (for Touchscreen) USB 2.0 Type A x 2 	 Mini D-Sub 15-pin (VGA) x 1 HDMI x 3 DisplayPort x 1 USB-A 2.0 x 3 (1 for upgrades) USB-B x 1 (for Touchscreen) USB-A 3.0 x 1 USB - C x 2 OPS x 1 Wireless Adaptor RJ-45 	 Mini D-Sub 15-pin (VGA) x 1 OPS x 1 HDMI x 2 USB-A 2.0 x 1 USB-B 3.0 x 3 USB-B 3.0 x 2 RJ-45 x 2 	 HDMI x 1 Wireless LAN Gigabit Ethernet (RJ-45) x 1 USB 3.0 Type A x 2 (for service) Bluetooth 4.0 LE
Video Output	▶ DisplayPort x 1	Display Port x 1	► HDMI x 1	► HDMI x 1	► N/A
Audio Input	> 3.5 mm Line In Jack x 1	> 3.5 mm Line In Jack x 1	▶ 3.5 mm Line In Jack x 1	▶ 3.5 mm Line In Jack x 1	► N/A
Audio Output	L/R Speaker Terminals x 1 pair	▶ 3.5 mm Line Out Jack x 1	> 3.5 mm Line Out Jack x 1	▶ 3.5 mm Line Out Jack x 1	▶ 3.5 mm Line Out Jack x 1
Control Terminals	RS-232C x 2 (Input & Output)RJ-45 x 1 on Controller	► RS-232C x 1 Input	▶ RS-232C	► RS-232C In/Out	► N/A
Physical Specifications	79.1" x 4.9" x 47.25"	76.81" x 3.87" x 45.75"	77.07" x 3.73" x 46.53"	79 75" v 5 75" v 49 60"	77.4" x 3" x 48.1"
Dimensions (WxDxH) Weight	79.1° x 4.9° x 47.25° 269 lbs.	170 lbs.	191.93 lbs.	78.75" x 5.75" x 48.62" 201 lbs.	220 lbs.
Product Warranty	3 Years	3 Years	N/A	3 Years	90 days
Notes	o rours	3 Tours	1 y /\	3 10013	Jo days
INA = Information not available N/A = Function not available		Includes 2 Wi-Fi antennas, Stylus x 2, Sharp Touch Viewing Software, Sharp Pen Software, Camera Mounting Kit, Sharp Display Connect License	 Dual Controller configuration with optional Windows Controller NUITEQ Stage (digital signage) 	▶ IQ and SmartMeeting Pro Included	 Monthly or annual subscription Closed Cisco Cloud architecture



Ricoh IFPD D8600BK Competitive Matrix

